

Printing date 07.06.2013

Revision: 07.06.2013

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY**Product Name: ESSENTIALS COLLECTION CATERING FUEL****Other Name:**

2,2-Oxydiethanol

2,2-Dihydroxydiethyl ether

2 hrs,3 hrs,4 hrs, 5 hrs,6 hrs

Product Code: EOS02, EOD04, EOD05, EOD06, RC04, RC06**Recommended Use of the Chemical and Restriction on Use:**

A liquid catering fuel. The fuel, diethylene glycol, is delivered via a wick protruding from a closed metal can. The product's wick is ignited and burned to provide heat for food warming applications.

Details of Manufacturer or Importer:

Easy Heaters Pty Ltd

3/15 Craftsman Avenue

Berkeley Vale NSW 2261

Phone Number: 02 4389 4144**Emergency telephone number:**

02 4389 4144 (Monday to Friday 6.00am to 3.00pm)

0437 909 557

2. HAZARDS IDENTIFICATION**Hazardous Nature:**

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

H227 Combustible liquid.

Label Elements**Signal Word** Warning**Hazard Statements**

H227 Combustible liquid.

H302 Harmful if swallowed.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS**Chemical Characterisation:** Substances**CAS No. Description**

111-46-6 2,2'-oxybisethanol

(Contd. on page 2)

Printing date 07.06.2013

Revision: 07.06.2013

Product Name: ESSENTIALS COLLECTION CATERING FUEL

(Contd. of page 1)

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

Ingestion:

Wash mouth with water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Information for Doctor

Symptoms Caused by Exposure:

Symptoms of exposure to this compound include nausea and vomiting. Other symptoms include headache, anuria, narcosis, cyanosis, tachypnea, tachycardia, hypotension, stupor, prostration, hypoglycemia and unconsciousness. Exposure can cause alcohol intoxication, muscle tenderness, pulmonary edema, convulsions and death.

5 . FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, dry powder, carbon dioxide (CO₂) and water spray jet.

Specific Hazards Arising from the Chemical

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Special Protective Equipment and Precautions for Fire Fighters

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.

6 . ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Ensure adequate ventilation.

7 . HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only in a well-ventilated area.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

(Contd. on page 3)

Printing date 07.06.2013

Revision: 07.06.2013

Product Name: ESSENTIALS COLLECTION CATERING FUEL

(Contd. of page 2)

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed. Protect from direct sunlight, heat/sparks/open flames/hot surfaces. Keep away from strong oxidising agents.

8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION**Exposure Standards (Safe Work Australia):****111-46-6 2,2'-oxybisethanol**NES 100 mg/m³, 23 ppm**Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapour below occupational exposure standards.

Personal Protective Equipment (PPE):**Respiratory Protection:**

Use a Safe Australia approved full face supplied air respirator if high airborne concentrations of the material are present. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Impervious gloves and protective clothing. See Australian Standards AS/NZS 2161, 2210.1 and 2210.2 for more information.

Eye and Face Protection:

Safety glasses with top and side shields or goggles. See Australian Standards AS/NZS 1336 and 1337 for more information.

9 . PHYSICAL AND CHEMICAL PROPERTIES**Appearance:**

Form:	Liquid
Colour:	Colourless
Odour:	Nearly odourless
Odour Threshold:	Not determined.
pH-Value:	7-8
Melting point/Melting range:	-6 °C
Initial Boiling Point/Boiling Range:	245 °C
Flash Point:	124 °C
Flammability:	Combustible liquid
Auto-ignition Temperature:	225 °C
Decomposition Temperature:	Not determined.
Explosion Limits:	
Lower:	1.8 Vol %
Upper:	12.2 Vol %
Vapour Pressure at 20 °C:	0.03 hPa
Relative Density at 20 °C:	1.1175-1.1195 g/cm ³
Vapour Density:	Not determined.
Solubility in Water:	Miscible
Viscosity at 20 °C:	38 mPas

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

(Contd. on page 4)

Printing date 07.06.2013

Revision: 07.06.2013

Product Name: ESSENTIALS COLLECTION CATERING FUEL

(Contd. of page 3)

Conditions to Avoid: Sources of ignition, open flame.

Incompatible Materials: Oxidising agents.

Hazardous Decomposition Products: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

Toxicity:

LD₅₀/LC₅₀ Values Relevant for Classification:

111-46-6 2,2'-oxybisethanol

Oral LD₅₀ 12565 mg/kg (rat)

Dermal LD₅₀ 11890 mg/kg (rabbit)

Acute Health Effects

Inhalation: May cause respiratory tract irritation.

Skin: May cause mild skin irritation. May be absorbed through the skin.

Eye: May cause mild eye irritation.

Ingestion:

Harmful if ingested. May cause liver and kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Human fatalities have been reported from acute poisoning.

Skin Corrosion / Irritation: Not expected to be a hazard.

Serious Eye Damage / Irritation: Not expected to be a hazard.

Respiratory or Skin Sensitisation: No sensitising effects known.

Germ Cell Mutagenicity: Not expected to be a hazard.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Not expected to be a hazard.

Specific Target Organ Toxicity (STOT) - Single Exposure: Not expected to be a hazard.

Specific Target Organ Toxicity (STOT) - Repeated Exposure: Not expected to be a hazard.

Aspiration Hazard: Not expected to be a hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic toxicity:

111-46-6 2,2'-oxybisethanol

LC50 0.3-1 mg/L (daphnia)

>100 mg/L (fish)

Persistence and Degradability: Biodegradation is expected to be an important fate process in water.

Bioaccumulative Potential: This product will exhibit low bio-concentration in aquatic organisms.

Mobility in Soil:

Estimated Koc value = 1. This value suggests that 2-Hydroxyethyl ether will have high mobility and be expected to biodegrade quickly in soil.

(Contd. on page 5)

Printing date 07.06.2013

Revision: 07.06.2013

Product Name: ESSENTIALS COLLECTION CATERING FUEL

(Contd. of page 4)

13 . DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 . TRANSPORT INFORMATION

UN Number

ADG, IMDG, IATA Void

Proper Shipping Name

ADG, IMDG, IATA Void

Dangerous Goods Class

ADG Class: Void

Packing Group:

ADG, IMDG, IATA Void

Marine pollutant: No

15 . REGULATORY INFORMATION

Australian Inventory of Chemical Substances:

111-46-6 2,2'-oxybisethanol

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:

Poisons Schedule: 6

16 . OTHER INFORMATION

Creation Date: 07.06.2013

Prepared by: MSDS.COM.AU Pty Ltd

www.msds.com.au

Abbreviations and acronyms:

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

Disclaimer

This MSDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Easy Heaters Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.